

INSTRUCTIONS

- al and/or subsequent record used to evaluate the corner position.
- Description of evidence found, note discrepancies in the record, state method of establishing corners.
- Description of monument and accessories set to perpetuate the corner position.
- Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- Fill in Cross Index & Section Diagram at bottom of sheet.

160949

CERTIFIED CORNER RECORDATION

Corner Northwest Sec 31 T.2 N R.58 E P.M.M. Carter County

ORIGINAL RECORD: An iron post, 3 ft long. 2 ins. in diam. 28 ins. in the ground, with brass cap marked:

T2N
 R57E R58E
S25	S30
 S36 | S31
 1944

FOUND: Found monument as per original record

SET: Monument in good repair no new monument set

S25	S30 S.88°03'00"W. S30
 S36 | S31 2660.97' S31



⊕brass cap (found)

SKETCH OF CORNER

CERTIFICATION

I, _____ certify the information shown herein is true and correct.

Jimme L. Brewer
Signature of Ground Party Chief

I, Jimme L. Brewer certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (22-101, et seq., M.C.A.)


Jimme L. Brewer
Signature of Surveyor & REGISTERED PROFESSIONAL LAND SURVEYOR

Date: 3-01-88
Employer: PRINCIPAL ENGINEERS, Inc

Office of Clerk and Recorder, County of Carter. This "corner record" was filed for record on June 17, 1988 was noted on the cross-index plat and is assigned page No. 186, in book No. 1

Sandra Kirkwood
County Official

Cross Index No. V-1 T. 2N R. 58E P.M.M.



• - corner this sheet

160949