

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography lies, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner SEC. COR. 7 & 18 T. 4 N R. 10 W P.M.M. DEER LODGE County
12 & 13 4 N 11 W

ORIGINAL RECORD - GLO AUGUST 1869


Set corner to Sections 7, 18, 12, 13 a post in mound of earth with pits marked stone as per instructions.

Also: refer to field notes dated 1891, Book 2476 for a reference tie.

EVIDENCE FOUND: None

PERPETUATION: Set 5/8" rebar with 2" aluminum cap marked Howard 8376 S (see sketch) at single proportionate distance. Set a steel fence post near monument.

Refer to Parcel "G" minor subdivision on file at the Clerk and Recorder's Office, Deer Lodge County Courthouse. Document #C.O.S. 193-B.



SKETCH OF CORNER

CERTIFICATION

I, JAMES NELSON
 certify the information shown herein is true and correct.

James Nelson
 Signature Ground Party Chief

I, GLENN R. HOWARD
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.) 8376 S

Glenn R. Howard
 Signature of Surveyor REGISTERED

Date: 7-18-94 Reg. No. 8376 S
 SURVEYOR

Employer: D J & A ENGINEERS

Office of Clerk and Recorder, County of Deer Lodge. This "corner record" was filed for record on August 1, 1994 was noted on the cross-index plat and is assigned page No. 340, in book No. 2 Morie Anderson - Deputy
 County Official

Sec. 18

Cross Index No. J - 1 T. 4 N R. 10 W PMM
J - 25 T. 4 N R. 11 W

• - corner this sheet