

INSTRUCTIONS

1. Original and sequen. cord used to evaluate the corner position.
2. Description of .ice found, note discrepancies in the record, state methoa of establi .it or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner OF SECTIONS 13, 14, 23, AND 24 T. 5N R. 13W P.M.M. DEERLODGE County

1. 1906 HENRY B. DAVIS AND EDWIN R. McLAIN

SET A GRANITE STONE, 16X8X6 INS., 11 INS. IN THE GROUND, FOR CORNER OF SECTIONS 13, 14, 23, AND 24, MARKED WITH 3 NOTCHES ON SOUTH AND 1 NOTCH ON EAST EDGE; FROM WHICH

- A PINE, 10 INS. DIAM., BEARS N40°E, 97 LKS. DIST., MARKED T5NR13WS13BT.
- A PINE, 5 INS. DIAM., BEARS S37°30'E, 17 LKS. DIST., MARKED T5NR13WS24BT.
- A PINE, 5 INS. DIAM., BEARS S40°W, 47 LKS. DIST., MARKED T5NR13WS23BT.
- A PINE, 8 INS. DIAM., BEARS N18°W, 55 LKS. DIST., MARKED T5NR13WS14BT.

1969 B.L.M. ROY LEEDY

THE CORNER OF SECTIONS 13, 14, 23, AND 24, AS DETERMINED FROM THE REMAINS OF THE ORIGINAL BEARING TREES:

- A STUMP, BEARS N40°E, 97 LKS. DIST., WITH NO VISIBLE MARKS.
- A STUMP HOLE, BEARS S40°W, 47 LKS. DIST., WITH FALLEN LOG MARKED T5NR13WS23BT, LAYING ALONGSIDE.
- A PINE, 10 INS. DIAM., BEARS N18°W, 55 LKS. DIST., WITH NO VISIBLE MARKS.

AT THE CORNER POINT

SET AN IRON POST, 30 INS. LONG, 2 1/2 INS. DIAM., 24 INS. IN THE GROUND, WITH BRASS CAP MARKED.

T5N R13W	
S14	S13
S23	S24

1969

FROM WHICH

- A PINE, 8 INS. DIAM., BEARS N60°E, 40 LKS. DIST., MARKED T5NR13WS13BT.
- A PINE, 5 INS. DIAM., BEARS S28°15'E, 39 LKS. DIST., MARKED T5NR13WS24BT.
- A PINE, 9 INS. DIAM., BEARS S86°W, 25 LKS. DIST., MARKED T5NR13WS23BT.

RAISE A COLLAR OF STONE, 2 FT. DIAM., AROUND THE IRON POST.

2. 1997 MIKE D. WELDON

FOUND A B.L.M. BRASS CAP ON 2 1/2 IN. DIAM. IRON POST, CAP MARKED AS SHOWN BELOW IN A COLLAR OF STONE. FROM WHICH


- A PINE, 12 INS. DIAM., BEARS N60°E, 25.5 FT. DIST., MARKED T5NR13WS13BT.
- A PINE, 9 INS. DIAM., BEARS S28°E, 25.4 FT. DIST., MARKED T5NR13WS24BT.
- A PINE, 12 INS. DIAM., BEARS S86°W, 16.4 FT. DIST., MARKED WITH PITCHED OVER SCRIBED FACE.
- A PINE, 12 INS. DIAM., BEARS N16°W, 36.3 FT. DIST., WITH MOSTLY OVERGROWN FACE.

4 FT. DIAM. X 2 FT. HIGH MOUND OF STONE BEARS SOUTH 5 FT.

3. 1997 MIKE D. WELDON

BEARING TREE SIGNS WERE AFFIXED TO THE FRONT AND LAND SURVEY MONUMENT SIGNS TO THE BACK OF THE BEARING TREES. REGISTERED LAND SURVEYOR, "RLS 7692-S" WASHERS WERE AFFIXED TO THE SIDE CENTER OF THE BEARING TREES AT THE BASE.

ANGLE IRON POST WITH PROPERTY BOUNDARY AND LAND SURVEY MONUMENT DECALS SET 2.0 FT. NORTHWEST.



SKETCH OF CORNER

CERTIFICATION


I, JOHN K. BUNCE II
 certify the information shown herein is true and correct
John K. Bunce II
 Signature Ground Party Chief

I, MIKE D. WELDON
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq. M.C.A.)
Mike D. Weldon
 Signature of Surveyor & Seal

Date: 4-98 Reg. No. 7692-S
 Employer: U.S. FOREST SERVICE

Office of Clerk and Recorder, County of DEERLODGE. This "corner record" was filed for record on May 14, 1998 was noted on the cross-index plat and assigned page No. 500 book No. 2

Barbara J. Vaughn, Deputy
 County Official



Cross Index No. N-21 T. 5N R. 13W P.M.

● - CORNER THIS SHEET