

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND AND ORIGINAL RECORD, IF KNOWN:

GLD SURVEY COMMENCED 6-15-1873

RECORD:

SET A SANDSTONE 15" X 10" X 7" - 10" IN GROUND, MARKED WITH 6 NOTCHES ON EAST AND ONE ON SOUTH EDGES

FOUND:

NO EVIDENCE AT OCCUPATION


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER:

DATE OF WORK 10-92

SET:

1 1/2" X 24" IRON PIPE WITH 2" GALVANIZED CAP

SKETCH WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY: (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE)



Surveyor's Seal




I, Gordon E. Sorenson certify that the information shown herein is true and correct, and further certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

[Signature] dated: 2/2/97

Gordon E. Sorenson, PE/RLS
Montana Reg. No. 2345ES

[Signature] dated: _____
Field Party Chief

DIAGRAM OF CORNER



Office of the Clerk and Recorder, GRANITE County, State of Montana:

This 'corner record' was filed for record on the 25th day of Feb, 1992, was noted on the cross index plat and is assigned page No. _____ in book No. _____

Time: 9:05 A M.

[Signature]
COUNTY OFFICIAL

34791

CROSS INDEX NO. V-1, T. 51N, R. 14W, PMM