

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND AND ORIGINAL RECORD, IF KNOWN:


G.L.O. SURVEY COMMENCED 6-15-1873
RECORD:
SET A SANDSTONE 12" X 12" X 7" - 8" IN GROUND
MARKED 1/4 ON WEST SIDE.

FOUND:
NO EVIDENCE AT OCCUPATION.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER:

DATE OF WORK 10-92
SET:
A 1 1/2" X 24" IRON PIPE WITH 2" GALVANIZED CAP

SKETCH WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY:
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE)



Surveyor's Seal




I, Gordon E. Sorenson certify that the information shown herein is true and correct, and further certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

[Signature] dated: 2/21/97
Gordon E. Sorenson, PE/RLS
Montana Reg. No. 2345ES

[Signature] dated: _____
Field Party Chief

DIAGRAM OF CORNER



Office of the Clerk and Recorder, GRANITE County, State of Montana:

This "corner record" was filed for record on the 25th day of Feb, 1997,
was noted on the cross index plat and is assigned page No. _____ in book No. _____

Time: 9:06 A M.

[Signature]
COUNTY OFFICIAL

34792 CROSS INDEX NO. T-1, T. 5 N, R. 14 W, PMM