

1. Original and or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner East 1/4, Section 16 T. 6 N R. 10 W P.M.M. Powell County

Original Record: Mound of Stone, Wood Post

Found: Mound of Stone, Decayed Wood Post

*Set 5/8" x 18" Rebar with Yellow Plastic Cap
 Marked "Hendrickson 29145" at center of
 Stone Mound, Rebuilt Mound with
 Additional stones. Adjoining corners
 not found, hence no measurements
 were made.*



SKETCH OF CORNER

CERTIFICATION

I, Jack C. Hendrickson
 certify the information herein is true and correct.

(Professional Seal of Jack C. Hendrickson, Registered Land Surveyor, Montana)

I, JACK C.
 certify that this Corner Record correctly represents
 work performed by me or under my direction in compli-
 ance with the "Corner Recordation Act"
 (70-22-01, et. seq., M.D.A.)

(Signature of Jack C. Hendrickson)
 Date: 6-1-94 No.: 29145
 Employer: Self

Office of Clerk and Recorder, County of Powell. This "corner
 record" was filed for record on the 17th day of June 1994
 at 10:05 AM
 was noted on the cross-index plat and is assigned page No. _____ in
 book No. _____

(Signature of Karl M. Rydlew)
 County Official

