


# CERTIFIED CORNER RECORDATION

Corner 1/4 SEC. 32/33 T. 6N R. 14W P.M.M. GRANITE County

ORIGINAL RECORD: GEO. W. IRVINE, 1873: 40.00 CHS. SET A SANDSTONE 15X7X6 IN. 10 IN. IN THE GROUND FOR 1/4 SEC. COR. MKD. 1/4 ON THE W. SIDE.

EVIDENCE FOUND: FOUND NO EVIDENCE OF THE ORIGINAL CORNER. DID FIND EXISTING FENCE INTERSECTION.

PERPETUATION: USING THE FENCE INTERSECTION AS THE BEST EVIDENCE OF THE ORIGINAL CORNER LOCATION, SET 5/8X24 IN. REBAR W/ 2 IN. ALUM. CAP. PLACED YELLOW SIGN ON FENCEPOST ADJACENT.



SKETCH OF CORNER

CERTIFICATION	
I, _____ certify the information shown herein is true and correct.	
Signature Ground Party Chief <b>HANS BOHRNSEN</b>	
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)	
Signature of Surveyor & Seal	
Date: <u>6/23/05</u>	Reg. No. <u>12243 LS</u>
Employer: <b>WILLOWROCK, INC.</b>	

**050131**  
 Recorded 06/29/2005 At 03:03 PM  
 BLANCHE PEDERSON, Cty Granite Clerk and Recorder  
 Fee: \$ , By Blanche Pederson

Cross Index No. X9 T. 6N R. 14W PMM

Sec. 32


● corner this sheet