

CERTIFIED CORNER RECORDATION

Corner: S $\frac{1}{4}$ Corner Sections 10 T. 8N. R. 26E. P.M.M. Musselshell Co.

Original Record 1884 GLO: "Set a sandstone 16x15x4 inches, 10 inches in the ground for $\frac{1}{4}$ Section Corner marked $\frac{1}{4}$ on N. Face, dug pits 18x18x12 inches E & W. of stone 5 $\frac{1}{2}$ feet distance and raised a mound of earth 1 $\frac{1}{2}$ feet high and 3 $\frac{1}{2}$ feet base alongside."

Subsequent Record: None.

Evidence Found 3/26/04: Found sandstone 15x3 inches 8 inches above ground firmly set vertically. No markings visible. Found Palmer (10807LS) 2 inch Aluminum Cap on N. side of stone marked as the $\frac{1}{4}$ corner. Aluminum cap is 0.35 feet N. of "center" of stone, & point used for GPS shot. Held stone as $\frac{1}{4}$ corner.

Re-Establishment: None

Perpetuation: None.

03-2020 PN.7003 June 30, 2006
CERTIFICATION

I, _____
Certify the information shown herein is true and correct.

Signature Ground Party Chief

I, Daniel W. McGee
Certify that this Corner Record correctly represents work performed by me or under my direction in compliance with The "Corner Recordation Act" (70-22-101, et seq. M.C.A.)

Daniel W. McGee
Signature of Surveyor & Seal

Date: SEPT. 2006 Reg. No. 5157 S


Employer: MCGEE AND COMPANY, Inc



SKETCH OF CORNER

Office: **264528** Fee \$.00
 Recorded: **MUSSELSHELL COUNTY**
 Recorded **10/16/2006 At 08:54 AM**
 Was by: **Jane E Mang. Clerk and Recorder**
 By: *Judith B. Hawkins* Deputy
 book no. _____

This "corner" _____
 _____, in _____



County Official

Cross Index No. J-15 8N R. 26E P.M.M. ● - corner this sheet