

Missoula County Control Point Datasheet

Monument Description: 1-1/2" Aluminum Cap MSLA CO

Project Name: ALL

Station Description: Section Corner


Date Visited: July 28, 2010

Monument Stability: B- GPS Visibility: B+

Observer: SEN - CLG

Quad. Name: Florence

T. 11 N. R. 20 W.



NAD 83 (2007) Lat/Long Position

46°39'38.589"N

114°03'59.762"W

NAVD 88 Elevation: 3195.8 sft.

Notes:

Need traffic cones.

T. 10 N. R. 20 W.

Photo of Monument



Photo Looking East



Photo Looking West



Point # 5859

To Reach: 2wd access.



Map of Area

'88 SEP 19 AM 8 28

Corner 35 36 1 T. 10&11N R. 20W P.M.M. Missoula County

CERTIFIED CORNER RECORDATION

INSTRUCTIONS

- Original and/or subsequent record must be filed in the corner station.
- Inscriptions of evidence found, and description of establishing set or delineated corners.
- Sketch of corner, show all pertinent data to perpetuate the corner permanently.
- Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking.
- Certification must be made of accuracy of the Registered Land Surveyor in State of Montana.
- File in Cross Index & Section Diagram at bottom of sheet.

RECORD #1: (October 9, 1872) G.L.O. Surveyed by Henry C. Rohleder. Set a post and charred stake for corners, 1, 2, 35 & 36 from which:
 A pine 20 in dia bears N65°W a dist of 25 lks.
 A pine 38 in dia bears N.E a dist of 18 lks.
 A pine 24 in dia bears S57°W a dist of 69 lks.
 A pine 17 in dia bears S13°E a dist of 47 lks.

RECORD #2: (Sept. 4, 1966) Corner Recordation Doc. #270887 Set a 31 inch 1-1/4 inch galvanized iron pipe 40 inches into the ground. NOTE: See Corner Recordation Doc. #270887 for more information.

RECORD #3: (August 4, 1976) Corner Recordation Doc. #400317 Set 1-1/2 in alum cap on 5/8 in rebar .05 ft. below surface in asphalt road. Alum. cap was set from ties. (NOTE: Road was paved in 1976.)

REFERENCE: A P-K nail 1.0 ft. up on West side R.R. fence post bears S25°E a dist of 38.77 ft.
 A P-K nail 1.5 ft. up on East side of power pole bears S1°E a dist of 38.05 ft.
 A P-K nail 1.5 ft. up on West side of power pole bears N1°W a dist of 29.49 ft.
 A P-K nail on top of corner fence post bears N60°W a dist of 67.72 ft. for course and distance.
 (NOTE: See C. of S. #610 for course and distance.)

FOUND: (August 8, 1988) A 1-1/2 in alum cap flush with asphalt road surface near center line.

REFERENCES: Found a P-K nail 1.0 ft. up West side of R.R. tie fence post, bears S40°E a dist of 38.77 ft.
 Found a P-K nail 1.5 ft up on East side of power pole bears S1°W a dist of 20.54 ft.
 Found a P-K nail 1.5 ft. up on West side of power pole bears N4°E a dist of 33.77 ft.
 Found a P-K nail on top of corner fence post bears N62°W a dist of 68.00 ft.

Yellow location tags on references.

SKETCH OF CORNER P-P-K

CERTIFICATION

L. Lawrence D. Rosenbaum
 Surveyor
 State of Montana

Horace S. Blain
 Registered Land Surveyor
 State of Montana

here Sept 19 1988
 Employer: MISSOULA COLLEGE

Office of Clerk and Recorder, County of Missoula Sec. 35-36
 record" was filed for record on the 19 day of 1988
 was noted on the cross-index plat and is assigned page No. 606 in
 book No. 284 MISSO County Official Blain
 T O R
 284-0606
 Check Index No. 2-21 T 10N R 20W P.M.M.

Corner Recordation Form or Other Supporting Document

Point # 5859