

Missoula County Control Point Datasheet

Monument Description: 1-1/2" Aluminum Cap 8643S

Project Name: Ninemile Storage

Station Description: 1/4 Corner


Date Visited: Oct. 31, 2008

Monument Stability: C GPS Visibility: B+

Observer: SEN

Quad. Name: Huson

T. 15 N. R. 22 W.



NAD 83 (2007) Lat/Long Position

47°01'23.423"N

114°22'00.807"W

NAVD 88 Elevation: 3210.4 sft

Notes:

Cap was bigger originally, but now it is very mangled. Monument was straightened to vertical position, base of monument was vertical and very solid.

Photo of Monument



Photo Looking North



Photo Looking East



Photo Looking Southeast



To Reach: 2wd access.



Map of Area

274 PAGE 0125

- INSTRUCTIONS**
1. Print and/or subsequent record used in evidence for the corner to which.
 2. Description of evidence found, size discrepancies in the record, clear method of establishing line or corner.
 3. Description of monument and accessories set to perpetuate the corner position.
 4. Description of monument and accessories which can best be shown in a sketch example, corner marking, topographic site, position of accessories, etc.
 5. Certificate must be signed and sealed by Registered Land Surveyor in State of Montana.
 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner $\frac{1}{4}$ $\frac{27}{34}$ T. 15 N., R. 22 W., P.M.M. Missoula County

RECORD: 1882
Set a post 3 ft. long, 3 ins. square, 24 ins. in the ground marked 1/4 S on north face from which:
A pine, 15 ins. diameter, bears N. 80° W., 40 lks. (29.04 ft.) dist. marked 1/4 S ET.
A pine, 14 ins. diameter, bears S. 40° W., 28 lks. (16.48 ft.) dist. marked 1/4 S ET.



1973:
We establish this corner by proportion between the northeast and northwest corners of section 34. To perpetuate this corner we set a 24 in. copper clad brass capped monument and established the following reference monuments:
A pine, 10 ins. diameter, bears N. 03° 30' W., 102.00 feet.
A pine, 8 ins. diameter, bears N. 81° 30' E., 89.00 feet.

FOUND:
No evidence of original corner.
A 1 1/2 in. brass cap marked as shown:
But broken off on east edge. This monument was found to be in the wrong position. Four corners were set in 1973 by proportional methods. One of these being the 1/4 corner between sections 26 and 27 which we found in 1987. Due to this find the proportional position of the remaining corners have changed. See sketch on back and C.O.S. Number.



MAINTENANCE:
At the corner position set a standard USDA drivable aluminum monument with 3 1/4 in. aluminum cap 1 in. below ground marked as shown:
We used existing RM trees described as follows:
A pine, 14 ins. diameter, bears N. 12° W., 78.32 ft. from the USDA Monument scribed RM.
A pine, 16 ins. diameter, bears S. 82° E., 75.55 ft. from the USDA Monument scribed RM.
Placed ET and Land Survey Monument signs.
Painted the blazes red.

CERTIFICATION
I, Eddo M. Flavi
Surveyor General of the State of Montana
do hereby certify that the above described corner represents with perfect accuracy the corner of the section 27 and 34 of T. 15 N., R. 22 W., P.M.M., M.D.A. as shown on the attached plat and is signed page No. 274-0125 in book No. 274-274 of the County Official Record.

USDA CAP 86435
CRS 271
AMSWORTH CAP

MONTANA LAND SURVEYORS ASSOCIATION
JAMES A. FLANSBURG
8643 S
SIGNED: Eddo M. Flavi
2-5-88 Reg. No. 86435
Employer: USFS

SKETCH OF CORNER

Office of Clerk and Recorder, County of MISSOULA. This "corner record" was filed for record on the 24 day of APR, 1988 was noted on the cross-index plat and is assigned page No. 274-0125 in book No. 274-274 of the County Official Record.

Cross Index No. V-15 T. 15N R. 22W P.M.M.

• Corner this sheet 274-0125

Corner Recordation Form or Other Supporting Document

Point # 5799