

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Section corner common to 17, 18, 19 & 20 T.16N., R.20., P.M.M.

RECORD JUNE 1901:

Set slate stone 16 12 5 ins., 11" in the ground.....Marked with 3 notches on South and 5 notches on East edges....From Which:

- A pine 7" diam bears N.39-3/4°E., 14 lks (9.2ft) marked T.16N., R.20W., S.17, B.T.
A pine 8" diam bears S.23-1/2°E., 50 lks (33.0 ft) marked T.16N., R.20W., S.20, B.T.
A pine 8" diam bears S.59°W., 43 lks (28.4 ft) marked T.16N., R20W., S.19, B.T.
A pine 6" diam bears N.10-1/2°W, 12 lks (7.9 ft) marked T.16N., R.20W., S.18, B.T.

EVIDENCE FOUND OCTOBER 1977:

At the corner position I find a slate stone 15 x 11 x 5 ins. pushed over with 3 notches on S and 5 notches on East. I accept the base of the stone as the true position, From which:

A stump hole with scribed face lying downhill marked T.16N., R20W., S.17, B.T., the stump

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

- Stump hole bears N.41°E., 9.1 ft
A pine stump 10" diam bears S.23-3/4°E., 32.9 ft marked S.20, B.T. Date of work: October 1977
A stump hole bears S.59-1/4°W, 28.5 ft
A stump hole with scribed face lying downhill marked T.16N., R.20W., S.18, B.T., the stump hole bears N.09°W., 8.2 feet.

THE FOUND POSITION I remove stone and in its place set a 2-1/2" brass cap affixed to a 2"x30" pipe marked as per diagram below, and bury stone along side.

NEW R.M.'s ESTABLISHED:

- A pine 6" diam bears N.30-1/2°E., 20.0 feet marked T.16N., R.20W., S.17, R.M.
A pine 10" diam bears S.32°E., 21.2 feet marked T.16N., R20W., S.20, R.M.
A fir 8" diam bears S.46-1/2°W, 27.6 feet marked T.16N, R.20W., S.19, R.M.
A fir 8" diam bears N.46-3/4°W., 18.9 feet marked T.16N., R.20W., S.18, R.M.
c. used 19-1/2"

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

new R.M.'s signed and painted red

SEE CERTIFICATE OF SURVEY NO. 1351

Surveyor's Seal

I, Paul S. Long certify that the information shown herein is true and correct.

Signature of Paul S. Long


Signature of Ground Party Chief

I, Robert S. Custer certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Robert S. Custer


Signature of Surveyor

DIAGRAM OF CORNER:



○ = Corner recorded on the sheet 2 1/2" Brass cap

33255 Registration Number



Office of Clerk and Recorder, County of Lake, State of Montana

This "corner record" was filed for record on the 19th day of DECEMBER, 1977, at 2:45 o'clock P. M.

signed by 238594, in book No. C-787 Ethel M. Harding, Lake County Clerk & Recorder By: Gloria L. Wilson, Deputy County Official