

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner: Sections 16 & 17 ONLY T. 16N R. 20W P.M.M. Lake County

1905 GLO: GLO Surveyor's Fredrick L. Cumming and George G. Webster, set a granite stone 18x10x6 ins., 10 ins. in the ground marked with 4 notches on south and east edges, for corner of Sections 8, 9, 16, and 17; from which:

- A 15" Fir bears N30°E, 40 lks (26.4'), mrkd T16N R20W S9 BT.
- A 7" Fir bears N52°W, 17 lks (11.2'), mrkd T16N R20W S8 BT.

Surveyors Cumming and Webster then run S0°04'W between Sections 16 & 17 from the corner just established for Sections 8, 9, 16, and 17 and fall 125 lks east of the Closing Corner for Section 16 and 17 on the Reservation Boundary, which was established by the 1901 GLO survey. As this line would be out of limits in alignment, they correct, and from the above described Closing Corner run N0°04'W between Sections 16 & 17 and set a quartzite stone 12 x 10 x 6 ins., 8ins., in the ground for Sections 16 and 17 marked with 4 notches on south and east edges. From this corner they establishes the following bearing trees:

- A 14" Fir bears S20°E, 122 lks (80.5'), mrkd T16N R20W S16 BT.
- A 14" Fir bears S82°W, 85 lks (56.1'), mrkd T16N R20W S17 BT.

Surveyors Cumming and Webster then state, corner of Sections 8 and 9, which I change for two sections bears East 125 lks (82.5').

1976 Record: Surveyor Christopher Balstad Jr. found corner of Sections 16 & 17 as well as the corner for Sections 8 & 9. From the Section corner common to Sections 16 & 17 Surveyor Balstad finds the Section 17 original bearing tree and creates one new bearing tree in Section 16. From the Section corner common to Sections 8 & 9 Surveyor Balstad finds a fir with a tag in Section 16, and a fir with face that could be a BT in Section 8. For further information see Recordation Form No. 228373 recorded in 1976, records of Lake County, Montana.

2007 Found: At the position for the section corner common to Section 16 & 17 only, we did not find the original stone. We did find the Section 17 original GLO bearing tree, which was a 26" Fir, and the Section 16 bearing tree established by Surveyor Balstad, which was a 24" Pine.

2007 Perpetuation: At a distance / distance intersection from the found bearing trees we set 5/8 x 24 inch rebar topped with a 3-1/4 inch aluminum cap 0.4' above ground. We stamped the monument as shown below and establish the following references:

- A 16" Fir bears S8°E, 41.8', blazed and scribed "RM2".

Found reference monuments are as follows:

- A 26" Fir bears S75°W, 56.1', with heel blaze.
- A 24" Pine bears S49°E, 38.9', with heel blaze.

References affixed with BT tags, a snow blaze, and a red band.

SKETCH OF CORNER

CERTIFICATION

I, Phil Tosh
certify the information shown herein is true and correct.
Phil Tosh
Signature Ground Party Chief

I, Ken E Jenkins
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, MCA).
Ken E Jenkins
Signature of Surveyor & Seal
9330LS

Date: 9/2007 Reg. No. 9330LS

Employer: Montana Northwest Company
PO Box 8777, Missoula, MT 59807
406-721-4033 Project No. 1592-07

Sec. 16

Office of Clerk and Recorder, County of Lake. This "corner record" was filed for record on SEP 17 2007 @ 2:07 PM

was noted on the cross-index plat and is assigned page No. _____ in

Book No. 483142

John E. Long
County Official

●			

Cross Index No. I-9 T. 16N R. 20W PMM

● - Corner this sheet

C-2737 N/C