

CERTIFIED LAND CORNER RECORDATION (REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

I found corner rock to be a quartzite rock about 8 x 8 x 12 inches, marked with 5 grooves on E and 1 groove on S side. (Record: Set a quartzite stone 12 x 12 x 8 inches, 8 inches in the ground, for corner to sections 29, 30, 31 and 32; marked with 1 notch on S and 5 notches on E edges.)

From the corner, I found a stump hole bearing N62°E, 50 lks. dist. (Record: A pine, 8 inches in diameter, bears N62 1/4°E, 50 lks. dist., marked T18N R27W S29BT.)

I found a decayed tamarack stump S24°E, 10 lks. dist., no marks visible. (Record: A tamarack, 1 1/4 inches in diameter, bears S24 1/2°E, 10 lks. dist., marked T18N R27W S31BT.)

I found a decayed tamarack stump S44°W, 6 lks. dist., no marks visible. (Record: A tamarack, 10 inches in diameter, bears S44 1/2°W, 6 lks. dist., marked T18N R27W S31BT.)

I did not find NWBT. (Record: A fir, 12 inches in diameter, bears N40 3/4°W, 6 lks. dist., marked T18N R27W S30BT.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner, I set a 1 1/2 x 30" GI pipe, 20 inches in the ground with a brass cap marked----- Date of work: 6/21/66

I placed original rock in the hole on the N side of the pipe. I piled a mound of rock around the pipe, 3 ft. base to top of cap.

I marked new RM's as follows:

- A 1 1/4" lodgepole pine bears S29°E, 93 lks. dist., marked "RM"
A power pole bears N80 1/2°W, 123 lks. dist., with a 4 penny nail and patch of blue flagging at base.
A power pole bears N28 1/2°E, 17 lks. dist., with a 4 penny nail and patch of blue flagging at base.

T18N R27W

S30 | S29
S31 | S32

1966

WJM-IM TILLOTSON 858 ES


SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal

I, William J. Morrow certify that the information shown herein is true and correct. Signature of Ground Party Chief

I, I. M. Tillotson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Signature of Surveyor

DIAGRAM OF CORNER:



◆ = Corner recorded on the sheet

858 ES MONT Registration Number

Office of Clerk and Recorder, County of

This "corner record" was filed for record on the 3rd day of March 1967, was noted on the cross-index plat and is assigned page No. 200 P.M., in book No.

Signature of County Official