

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

CORNER: $\frac{3}{10} | \frac{2}{11}$ T.18N., R.27W., PRINCIPAL MERIDIAN, MT., MINERAL CO., MONTANA

G.L.O. NOTES: Page & Page, 1893

Set a post 4 ft. long, 4 ins square, 24 ins. in the ground, for cor. to sec's. 2, 3, 10 & 11 marked T18N S2 on NE, R27W S11 on SE, S10 on SW and S3 on NW faces, with 5 notches on S. and 2 notches on E. edges; From which

- A 18" pine bears N.53°E., 162 lks. (106.9') dist. marked T18N R27W S2 BT
- A 14" Larch bears S.38°E., 133 lks. (87.8') dist. marked T18N R27W S11 BT
- A 11" Larch bears S.41°W., 48 lks. (31.7') dist. marked T18N R27W S10 BT
- A 16" Larch bears N.49°W., 61 lks. (40.3') dist. marked T18N R27W S3 BT

WE FIND:

1/2" rebar w/ 1" Y.P.C. mkd. Warren 2734S - corner has been accepted as section corner in other surveys. We accept rebar as sec. corner.

All trees have been cleared and section corner falls in middle of farmed field.

TO PERPETUATE THE CORNER WE:

Replace rebar w/ 2 1/2" x 30" al. mon., buried 28" in the ground, rebar is removed from the site. Monument is collared w/ stone.

A RR tie bears West 4.4 ft BEARING TREE & LAND SURVEY MONUMENT signs are nailed to post.

Notes: See Certificate of Survey recorded by this surveyor @ Mineral Co. Court house.

Equipment used: Project No. 93-3722, Donlan 2a

SKETCH OF CORNER

MONTANA

STEVEN M. INABNIT
9328 S
REGISTERED PROFESSIONAL LAND SURVEYOR

CERTIFICATION

I, _____ certify the information shown herein is true and correct.

Signature Ground Party Chief
Steven M. Inabnit

This Corner Record correctly represents work performed under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq. M.C.A.)


Signature of Surveyor & Seal
Steven M. Inabnit

Date: 3/1995 Reg. No. 9328 LS

Employer: ELI & ASSOCIATE

Office of Clerk and Recorder, County of Mineral. This "corner record" was filed for record on the August 28th day of 1995 at 11:12 A.M. was noted on the cross-index plat and is assigned page No. _____, in book No. _____

Shirley Mancini by Anita White
County Official



Cross Index No. E 17 T. 18N R. 27W PMM