

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

224356

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)


Found Rock painted Red, loosely set.
Found Bearing Trees as follows:

- A 6" Fir bearing S 62 W, 49.5'. Marked same by Chris Balstad. #3322S
- A 18" Pine bearing S 30 E, 14 Links. Marked same.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct 30, 1973

Set a 1" Pipe with a 2" Brass Cap in accordance with Bearing Trees available. Placed the original stone in Mound around the Brass Cap.
Brass Cap marked as shown:



SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal




I, MIKE WENTZ.....STIEVE DAY.....
certify that the information shown herein is true and correct.

Michael K. Wentz, Stephen H. Day
Signature of Ground Party Chief

I, WILLIAM D. BAYER.....
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

William D. Bayer
Signature of Surveyor

DIAGRAM OF CORNER:



◆ = Corner recorded on the sheet

3321S
Registration Number

Office of Clerk and Recorder, County of LAKE, STATE OF MONTANA

This "corner record" was filed for record on the 3rd day of November 1975 at 4:38 o'clock P.M.
assigned page No. 224356, in book No. C-606

Ethel M. Harding, Clerk & Recorder
County Official By: *S. Wilson*, Dep

Cross Index No. R-13 T. 20N R. 19W P.MMer.