

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the section corner of Sections $\frac{5}{8} | \frac{4}{9}$, T.20 N., R.20 W., P.M.M., Lake County, Montana,

RECORD: Set a slate stone, 20"x8"x5", 15 in. in the ground for corner of section 4,5,8, and 9, marked with 5 notches on S and 4 notches on E edge, dig pits, 18"x18"x12" in each Sec. 5-1/2 ft dist. and raise a mound of earth, 4 ft base 2 ft high west of corner

WE FIND: Nothing

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 4/25/78

TO PERPETUATE THIS CORNER WE SET A:

1-1/2"x30" iron pipe with 2" brass cap 18" under surface of road, FROM WHICH


- A fence cor. bears N.45°E., 42.1 ft.
A fence cor. bears S.45°E., 41.85 ft.

References display MARLS corner tags with information on them.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. _____

Surveyor's Seal




I, Stephen H. Day, certify that the information shown herein is true and correct.

Signature of Stephen H. Day, Signature of Ground Party Chief

I, R. David Schurian, certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of R. David Schurian, Signature of Surveyor

DIAGRAM OF CORNER:



= Corner recorded on the sheet

3102S Registration Number

Office of Clerk and Recorder, County of Lake, State of Montana

This "corner record" was filed for record on the 21st day of AUGUST, 1978, at 11:33 o'clock A.M. was noted on the cross-index plat and is

assigned page No. 243267, in book No. C-815 Ethel M. Harding, Lake County Clerk & Recorder County Official By A. Wilson, Dep.

Cross Index No. E-9 T.20N R.20W P.M. Mer.