

INSTRUCTIONS

1. Original and/or subsequent records evaluate the corner position.
2. Description of evidence found, no. in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner S14 | S13 S23 | S24 T. 21N. R. 29W. P.M.M. Sanders County

GLO RECORD (1889): Set a sandstone, 20x9x4 ins., 15 ins. in ground for sec.cor. to secs. 13,14,23 & 24. Established 4 BTs.

RECORD - 1974 (COS #51 - Ainsworth, #2923S): "Found stone" (which shows as being used for single proportionment of 1/4 corner common to Sections 13 & 14.) (No corner form of record)

RECORD - 1987 (COS #890 - Sands, #7975S): "Found 3" aluminum cap by 2743S" (which shows as being used for single proportionment of 1/4 corner common to Sections 13 & 14) (No corner form of record)

FOUND - 1989 (100th anniversary of corner): Found a 2 1/2" aluminum pipe w/3 1/4" aluminum cap, marked as noted below, 0.4' above surface of mound of rock, which is at the base of a large rock pile at the edge of a Northerly bench. (Large rock pile appears to be field rocks, picked from adjacent fields and dumped here) (No corner form of record)

NOTE: A review of COS#51 and COS#890 indicates that the position of this monument is some 26.2 feet South of the position of the stone found by Ainsworth in 1974 and shown on COS#51.

See Certificate of Survey No. 995



SKETCH OF CORNER

CERTIFICATION

I, Duane Schmitz

certify the information shown herein is true and correct

Duane Schmitz
Signature of Grounds Chief

I, Richard A. Ainsworth

certify that this Corner Record accurately represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101 et seq., M.C.A.)

Richard A. Ainsworth
Signature of Surveyor & Seal


Date 11/89 Rec. No. 2923S

Employer: PROFESSIONAL CONSULTANTS

Office of Clerk and Recorder, County of Sanders. This "corner record" was filed for record on the 12 day of Jan 19 90, was noted on the cross-index plat and is assigned page No. 3, in book No. 339

Sally Clauson
County Official

Cross Index No. N21 T. 21N R. 29W P.M.M.



• corner this sheet