

CERTIFIED CORNER RECORDATION

Corner 6 | 5 T. 22N R. 19W P.M.M. Lake County

1904 G.L.O. Survey By William K. Trippet Book 4596 Page 56

"Set a slate stone, 12x12x10 ins., 8 ins. in the ground, for 1/4 sec. cor., marked 1/4 on W. face; from which:
A Willow, 4 ins. dia., bears N.53E., 80 lks. dist., marked 1/4 S 5 B T.
A Willow, 9 ins. dia., bears N.13W., 63 lks. dist., marked 1/4 S 6 B T."

1984 Corner Recordation by Christopher Balstad Jr., 3322ES, CR# C-1355

"IN 1973, AN ACCESS ROAD WAS CONSTRUCTED BY CANMONT CORP. ON SECTION LINE, THE INTERSECTION OF E-W AND N-S RETAINING WALLS AT END OF ROAD FALLS ON TOP OF 1/4 COR. LOCATION. A SURVEY BY SORENSON & CO. IN DEC. 1983 INDICATES THAT 1/4 COR. STONE WAS FOUND UNDER SAID RETAINING WALL. I DUG IN AND UNDER SAID WALL FINDING THE STONE IN PLACE. I FOUND A 3/4" PIPE AT COR. OF RETAINING WALLS WITH A RED TOP STAKE, BOTH BEING UNDER 6" OF FILL. IN THE COURSE OF MY TRAVERSE, I FOUND THE DISTANCE FROM THE SECTION COR. TO THE 1/4 COR. TO CHECK WITHIN .08' OF SORENSON'S SURVEY, AND THE BEARINGS TO CHECK WITHIN 10 SECONDS OF SAID SURVEY."

2000 Remonumentation by S. R. Smith

I find the original stone, 3 ft (.09 m) below ground surface on the east side of a fishing access road. Stone is on west side of old wood retaining wall and partially under base of wall. I removed stone and cleaned, to check for markings. Stone is slate, "10x12x12", with evidence remaining of portions of the "1/4" on the smooth west face. Replaced stone in its original position and buried. Directly above stone, I set a standard M.D.T. aluminum monument, which consists of a 2 1/4 ins (5.715 cm) diameter, 30 ins (76.2 cm) long aluminum pipe with flared base and 3 1/4 ins (8.255 cm) diameter M.D.O.T. aluminum cap, stamped as shown below. Top of cap is 1 ft (30 cm) below the road surface. Divit in center of cap is directly over the center of mass of the original stone, from which:

A 3/4 ins (1.905 cm) diameter, 5 ft (1.524 m) long aluminum conduit for witness post, with survey decal bears N80° East 0.40 ft (0.13 m).

A timber piling, with a 1 5/8 ins (3.33 cm) diameter brass disc, marked "SMITH 4740LS", set 1 ft (30 cm) above ground on the north face, bears N86° E 22.506 ft (7.384 m) distant.


An alder, 6 ins (15.24 cm) DBH, bears N23°W 113.96 ft (37.39 m) distant, scribed 1/4 S BT.

Note: Found 3/4" pipe driven beside stone, bears S30°E 0.085 m from corner position.

Bearings listed above in remonumentation section were measured with a hand compass, declination 18° East.

Refer to the Certificate of Survey filed in conjunction with this corner recordation for ties to adjacent section controlling corners.

See sketch of corner on reverse side of page.



SKETCH OF CORNER

CERTIFICATION

I, Robert K. Wunderlich, certify the information shown herein is true and correct.

Robert K. Wunderlich
Signature of Ground Party Chief

I, S. R. Smith, certify that this Corner Record, correct, represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-1017 & 805, M.C.A.)

S. R. Smith
Signature of Surveyor & Seal

Date: 12/31/00 Reg. No. 4740LS

Employer: Smith Surveying


Office of Clerk and Recorder, County of Lake. This "corner record" was filed for record on JUN 04 2001 1:15 pm

was noted on the cross-index plat and is assigned page No. 416238, in book No. C-2385

RUTH E. HODGES
County Official

Cross Index No. C-5 T. 22N R. 19W PMM

Sec. 6



corner this sheet
stalling/poleon-sast/cornercc\115A