

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

RECORD: Set a trap rock, 15x7x5 inches, 10 inches in the ground, for 1/4 section corner, marked 1/4 on West face; and raised a mound of stone, 2 ft. base, 1 1/2 ft. high W. of corner. Pits impracticable.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 5-10-78

TO PERPETUATE THIS CORNER WE: Set a 1"x24" iron pipe with a 2" brass cap marked as below, from which:

- An "x" on boulder bears S.28°00'W., 81.70 Feet.
- A nail in R/R tie bears N.87°00'W., 22.00 feet.
- A nail in R/R tie bears N.05°00'E., 9.68 feet.
- An "x" on boulder bears N.76°00'E., 113.35 feet.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

PLAT OF JETTE MEADOWS PHASE I. See Certificate of Survey No. _____

Surveyor's Seal



I, Gerald McCarthy certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, THOMAS M. HANSON certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:



Corner recorded on the sheet

3153 ES Registration Number

Office of Clerk and Recorder, County of Lake State of Montana

This "corner record" was filed for record on the 24th day of July 1979, at 10:30 o'clock A.M. and is signed page No. 249539, in book No. C-898

By: Roxanne Hartsoch, Deputy County Official

Cross Index No. P-25 T. 23N R. 20W Mer.

21 W

Lake Co