

CERTIFIED LAND CORNER RECORDATION

61-249540

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

RECORD: Set a slate stone, 14"x8"x6", 10" in the ground, for 1/4 section corner, marked 1/4 on N. face; and raised a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of corner. Pits impracticable.

FOUND: We searched area and could not find evidence of stone or mound of stones. There is a fence that runs E., W., & North with R/R tie corner. We accept this fence corner.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 4-18-79

TO PERPETUATE THIS CORNER WE: Set a 2"x30" iron pipe with a 2 1/2" brass cap, from which:

- An 8"x8" post & nail bears N.09° 00'W., 8.64 feet.
- An 8"x8" post & nail bears West 9.14 feet.
- An 8"x8" post & nail bears N.76° 00'W., 121.22 feet.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

PLAT OF JETTE MEADOWS PHASE I.  
See Certificate of Survey No. \_\_\_\_\_

Surveyor's Seal



I, Gerald McCarthy  
certify that the information shown herein is true and correct.

*Gerald M<sup>c</sup>Carthy*  
Signature of Ground Party Chief

I, THOMAS M. HANSON  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

*Thomas M. Hanson*  
Signature of Surveyor

DIAGRAM OF CORNER:



3153 ES  
Registration Number

Office of Clerk and Recorder, County of Lake State of Montana  
This "corner record" was filed for record on the 24<sup>th</sup> day of July 1979, at 10:32 o'clock A.M.  
signed page No. 249540, in book No. C-899  
By: Roxanne Hartsock Deputy  
County Official

Cross Index No. R-3 T. 23N R. 20W Mer.