

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the full corner common to Sections 28, 29, 32 & 33, Township 23 North, Range 30 West, Sanders County, Montana.

RECORD: Set a post 4' long, 4" Sq., 24" in the ground for cor. to Secs. 28, 29, 32 & 33 from which:
 A fir 8" bears N.14°E., 49 links
 A Fir 8" bears S.25°E., 77 links
 A Fir 6" bears S.14°W., 75 links
 A Fir 8" bears N.83°W., 21 links

WE FIND: No evidence of original corner.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 3/20/74


WE ESTABLISH this corner by land use lines.

TO PERPETUATE this corner we set a 5/8"x18" rebar with aluminum cap in asphalt road and establish the following reference monuments:

- A 14" Pine bears S.16°00'E., 97.7 feet
 - A 15" Pine bears N.16°00'W., 74.8 feet
 - A 16" Pine bears S.19°00'W., 47.4 feet
 - A 20" Pine bears N.64°00'E., 165.16 feet
- Variance used 20°

All scribed "R.M."

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal




I, GREGORY S. MARTINSEN
 certify that the information shown herein is true and correct.

Richard A. Ainsworth
 Signature of Ground Party Chief
 RICHARD A. AINSWORTH

I, _____
 certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

R. Ainsworth
 Signature of Surveyor

DIAGRAM OF CORNER:



◆ = Corner recorded on the sheet

AINSWORTH & ASSOCIATES 2923S 138849
 Registration Number

Office of Clerk and Recorder, County of Sanders 8:30 am
 This "corner record" was filed for record on the 29 day of Dec 1976, was not d on the cross-index plat and is assigned page No. 603, in book No. 1
Dixie Thayer Linda Brown
 County Official
 FORM 125 - 41483 VOL 1 PAGE 603 Cross Index No. V9 T. 23N R. 30W Mer.