

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the One-Quarter corner common to Sections 28 & 33, Township 23 North, Range 30 West, Sanders County, Montana.

RECORD: Set a post 3' long, 8" square, 24" in the ground for 1/4 Sec. Cor. marked 1/4 S on North face from which:
 A balsam 8" bears N.55°W., 56 links
 A Pine 13" bears S.55°W., 50 links

WE FIND: No evidence of original corner and BT's.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 4/23/74


WE ESTABLISH this corner by single proportionment between the SW & SE corners of Sec. 28

TO PERPETUATE this corner we set a 24"X5/8" copper clad brass capped monument and establish the following reference monuments:

- A 10" Pine bears S.74°00'W., 10.30 feet
- A 10" Pine bears S.81°00'E., 4.65 feet
- A 12" Fir bears S.33°00'W., 15.45 feet

Variance used E.20°

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal




I, GREGORY S. MARTINSEN certify that the information shown herein is true and correct.

Richard A. Ainsworth
 Signature of Ground Party Chief
 RICHARD A. AINSWORTH

I, _____ certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

R. Ainsworth
 Signature of Surveyor

DIAGRAM OF CORNER:



● = Corner recorded on the sheet

AINSWORTH & ASSOCIATES

2923 S
 Registration Number

139856

Office of Clerk and Recorder, County of Sanders, 8:24 am

This "corner record" was filed for record on the 29 day of Dec, 1976, was noted on the cross-index plat and is assigned page No. 600, in book No. 1

Deji Taught by Linda Brown
 County Official