

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

¼ Corner Sections 27 & 34 T. 25 N. R. 18 W. P.M.M. Lake County

ORIGINAL RECORD: (1935 G.L.O.) Not recovered.

EVIDENCE FOUND: Found 2½" brass cap, 0.8' above ground with aluminum witness post 0.25 ft. south. Cap orientation is south instead of north.

Monument lies approximately 30 ft. south of two track and approximately 210 ft. east of Crane Mt. Road.

PERPETUATION: A 6" pine bears S55°W, a distance of 5.0 ft, affixed BT tag.

Date of Survey: October, 2010.



NAD 83 coordinates for this corner:
 Latitude = 47°53'31.748"N Longitude = 113°52'02.41"W
 NOTE: These coordinates are to be used as a search tool only.

CRANE MT. ROAD	<p>(Not to Scale) SKETCH OF CORNER</p>	<p style="text-align: center;">CERTIFICATION</p> <p>I, <u>Steve Cummings</u> certify the information shown herein is true and correct.</p> <p style="text-align: center;">_____ Signature Ground Party Chief</p> <p>I, <u>Kurt A. Luebke</u> certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)</p> <p style="text-align: center;">_____ Signature of Surveyor & Seal</p> <p>Date: <u>11-22-2010</u> Reg. No. <u>13237 S</u></p> <p>Employer: <u>DJ&A P. C.</u></p>
----------------	--	---

