

INSTRUCTIONS

1. Initial and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or omitted corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

**CERTIFIED CORNER RECORDATION**

Corner Sec. 4, 5, 8 & 9 T. 25N R. 32W P.M.M. Sanders County

RECORD 1982: THE COR. OF SECS. 4, 5, 8, AND 9, MONUMENTED WITH AN IRON POST, 2 1/2 INS. DIAM., FIRMLY SET, PROJECTING 8 INS. ABOVE THE GROUND, WITH BRASS CAP MKD.

T25N R32W  
 S 5 | S 4  
 S 8 | S 9  
 1977

FROM WHICH BEARING TREES ESTABLISHED BY THE FOREST SERVICE IN 1965:

A FIR, 12 INS. DIAM., BEARS N. 46° E., 56 LKS. DIST., MKD. RM.

A FIR, 10 INS. DIAM., BEARS S. 33° W., 50 LKS. DIST. MKD. RM.

AND THE 1977 BEARING TREES:

A FIR, 12 INS. DIAM., BEARS S. 58° E., 55 LKS. DIST., MKD. T25N R32W S9 BT.


A LARCH, 12 INS. DIAM., BEARS N. 79° W., 54 LKS. DIST., MKD. T25N R32W S5 BT.

THIS COR. WAS REMONUMENTED BY LARRY A CHRISTIANSEN, CADASTRAL SURVEYOR, UNDER GROUP NO. 611, MT., IN 1977.

FOUND: 3 1/4" DIAMETER BRASS CAP STAMPED PER THE 1982 RECORD FROM WHICH:  
 A 14" LARCH W/BLAZE AND SCRIBE BEARS N 79° W, 54 LINKS DISTANCE  
 A NEW BEARING TREE, A 10" DIAMETER FIR, BEARS N 35° E, 19.9 FT.  
 ALL OTHER BEARING TREES PER THE 1982 RECORD HAVE FALLEN OVER.

SEE CERTIFICATES OF SURVEY NOS. 1276 AND 1277 FOR TIES TO ADJACENT CORNERS.

T25N R32W  
 S 5 | S 4  
 S 8 | S 9  
 1977



209888

SKETCH OF CORNER

CERTIFICATION

I, William W. Weikel  
 certify the information shown herein is true and correct.

Signature Ground Party Chief

I, William W. Weikel  
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act", 70-22-101, et seq., M.D.A.


[Signature]  
 Signature of Surveyor & Seal

Date: 8-93 Reg. No. 4731LS

Employer: WGM group

Office of Clerk and Recorder, County of Sanders. This "corner record" was filed for record on the August 27, 1993 @ 8:15am day of 1993 was noted on the cross-index plat and is assigned page No. 3 957, in book No. \_\_\_\_\_

Dip Vaught By Patricia Mengraham  
 County Official



Cross Index No. E-9 T. 25N R. 32W P.M.M.

• - corner this sheet