

INSTRUCTIONS

1. Description of monument and accessories set to perpetuate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Sec 32 & 33 26N T. 25N R. 32W P.M.M. Sanders County
Sec 4 & 5

RECORD 1982: POINT FOR THE COR. OF SECS. 4, 5, 32, AND 33, AT PROPORTIONATE MEASUREMENT. THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL COR.

SET AN ALUMINUM POST, 30 INS. LONG, 2 1/2 INS. DIAM., FLUSH WITH THE SURFACE OF THE GROUND, WITH ALUMINUM CAP MKD.

T26N R32W
S 32 | S 33
S 5 | S 4
T25N R32W
1983

FROM WHICH

THE SE. COR. OF A CONCRETE GARAGE, BEARS N. 73° E., 69 LKS. DIST.

THE MK. "X," CHISELED ON A METAL LIGHT POLE, BEARS S. 44° E., 23 LKS. DIST.

A CEDAR, 12 INS. DIAM., BEARS S. 44° W., 82 LKS. DIST., MKD. T25N R32W S5 BT.

THE COR. IS SITUATED 32 LKS. SW. OF THE CENTERLINE OF A GRAVEL ROAD, BEARS NW. AND SE., IN THE YARD OF THE SUBSTATION JUST BELOW NOXON RAPIDS DAM.

FOUND: 3 1/4" DIAMETER ALUMINUM CAP PER 1982 RECORD, FROM WHICH THE SE CORNER OF A GARAGE BEARS N 73° E, 41.4 FT.

AN "X" IN LIGHT POLE BEARS S 44° E, 15.2 FT.


A 10" PINE WITH BLAZE AND TAG BY SURVEYOR 5616S BEARS S 39° W, 34.1 FT.

SEE CERTIFICATE OF SURVEY NO. 1276 FOR DIMENSIONS TO OTHER CORNERS.

T26N R32W
S 32 | S 33
S 5 | S 4
T25N R32W
1983

209889

SKETCH OF CORNER



CERTIFICATION

I, William W. Weikel
certify the information shown herein is true and correct.

Signature Ground Party Chief

I, William W. Weikel
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

[Signature]
Signature of Surveyor & Seal


Date: 8-93 Reg. No. 4731LS

Employer: WGM group

Office of Clerk and Recorder, County of Sanders. This "corner record" was filed for record on the August 27, 1993 @ 8:20 am day of 1993 was noted on the cross-index plat and is assigned page No. 3 958, in book No. _____

[Signature]
County Official

Cross Index No. Z-9 26N
A-9 T. 25N R. 32W P.M.M.



• - corner this sheet