

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner

33	34
4	3


 T. 26N R. 32W P.M.M. Sanders County

RECORD: Original G.L.O. Record:
 Set a pine post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 3, 4, 33 and 34, marked:
 T 26 N S 34 on NE.,
 R 32 W S 3 on SE.,
 T 25 N S 4 on SW., and
 S 33 on NW., face, with 3 notches on E. and W. edges; from which:
 A 7" tamarack bears N.42½°E., 70 lks. dist., marked T26NR32WS34 BT
 An 8" fir bears S.64¼°E., 40 lks. dist., marked T25NR32W S3 BT.
 A 7" tamarack bears S.66½°W., 119 lks. dist., marked T25NR32W S4 BT.
 A 6" fir bears N.23¼°W., 46 lks. dist., marked T26NR32W S33 BT.

FOUND: No evidence of original corner.

SET: At the proportioned position we set:
 A 3¼" aluminum cap on a 2½" x 30" aluminum pipe., 22" in the ground with mound of stone.
 A 12" white pine bears S.32°E., 53.1 ft. marked T25NR32W S3 BT
 A 13" yellow pine bears S.62°W., 76.3 ft. marked T25NR32W S4 BT
 An 8" fir bears N.81°W., 108.9 ft. marked T26NR32W S33 BT.
 No practical BTs in Northeast quadrant.

Corner falls 11 ft. Southwesterly of centerline of access road on Southside of railroad tracks.



BOOK 2 PAGE 492

SKETCH OF CORNER

CERTIFICATION

I, Ken Jenkins
 certify the information shown herein is true and correct.
Ken Jenkins
 Signature of Ground Party Chief

I, R. David Schurian
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-23101 et seq., M.C.A.)
R. David Schurian
 Signature of Surveyor & Seal

Date: 9/83 Reg. No. 3102S
 Employer: Professional Consultants, Inc.

Office of Clerk and Recorder, County of Sanders. This "corner record" was filed for record on Nov 17, 1983 was noted on the cross-index plat and is assigned page No. 492, in book No. 2 by Lizette Vaught Clerk County Official

