

CERTIFIED LAND CORNER RECORDATION

Section 4 Twp. 30 N., R. 31 W., M.P.M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

SEE SKETCH ON BACK

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: May 1970

- Cor. #1 Set a pipe 18' long driven flush to pavement
Cor. # 2 Set a Boat spike in pavement from which a power pole bears N 17°30'W 17.2 Ft.
a Power pole bears S 46° E 27.3 Ft.
Cor. #3 Set a steel rod
Cor. #4 Set a 3/4" pipe 2 ft. long from which a 10" Fir bears N 12°30'W 33.3 ft. scribed C 1/16 S and Posted
a 16" Fir bears S 53°30'W 38.3 ft. scribed C 1/16 S and Posted
Cor. #5 Steel axle by others

SEE SKETCH ON REVERSE SIDE

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE REVERSE SIDE

DIAGRAM OF CORNER:

Surveyor's Seal

I, Jack H. Ninneman certify that the information shown herein is true and correct.

Signature of Ground Party Chief

N. Sec. 4 Twp. 30 N., R. 31 W M.P.M. Sketch on reverse side

I, Jack W. Ninneman certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

= Corner recorded on the sheet

534 ES Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 30th day of November 1970, was noted on the cross-index plat and is assigned page No. 208, in book No. 1

ELEANOR L. VAUGHN, By: Mae Watson County Official Deputy

Cross Index No. T. 30 R. 31 Mer.

A-9 A-11 B-11 C-9, 11, 12, 13 D-11, 12