

**AMENDED
CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found a large mound of stone with a 4"x4" wood post at the center of the mound. Approximately 3 feet to the south of the center of the mound an unmistakable depression was found with a 5/8" rebar, 8.5" above ground on the west side of the depression. Lying loose, 2-foot south of the depression, found the original stone measuring 7"x12"x13" with 3 slashes on one side, 2 slashes on another side and a chiseled cross on a third side. Testimony of various sources state that this stone was formerly in the said depression with the cross on the top of the stone. The stone was probably dislodged by the setting of the 5/8" rebar. To the south of this found evidence, four old survey monuments were found which were included in a survey made by Thomas J. Hallin and L.T. Christian in 1953. A retracement survey of these points confirmed that the bearings and distances between them are very nearly as reported in 1953 and the tie between them and the cross on the stone when

(over)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set a 2" diameter by 24" aluminum pipe with a flared footing with an aluminum cap marked as shown below for the corner common to Sections 15, 14, 22 and 23, T.9S., R.8E. Buried the original stone approximately 7" to the southeast of the aluminum monument with 3 slashes on the east and 2 slashes on the south and the cross on top. The top of the monument is 8.5" above ground and the foot of the monument rests on the travertine bedrock. Built a 2-foot diameter by 1-foot high mound of stone around the monument. The 5/8" rebar bears S 85°20'48" W, 0.73 feet. The top of the wood post in the large mound of stone bears N 42°32'16" E, 3.38 feet. A 1 1/8" diameter drill stem, 11" above the ground set in a 3-foot diameter ring of stone, found during the 1953 Hallin-Christian survey bears S 0°04'21" W, 452.80 feet.


Date of work: 10-30-80

(over)

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE REVERSE SIDE

Surveyor's Seal



I, Fred L. Hall
certify that the information shown herein is true and correct.


Fred L. Hall
Signature of Ground Party Chief

I, Thomas J. Hallin
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Thomas J. Hallin
Signature of Surveyor

DIAGRAM OF CORNER:

N. SECTION CORNER



T. 9 S. R. 8 E.

= Corner recorded on the sheet

287ES

Registration Number

165609

Office of Clerk and Recorder, County of Park

This "corner record" was filed for record on the 10th day of June 1981, was noted on the cross-index plat and is assigned page No. 21-A, in book No. one @ 4:22 P.M.

Margaret Monice
County Official

Form 125
State Publishing Co., Helena, Mont.

Cross Index No. N.17 T. 9S R. 8E Mer.

Fee 504 (Amended 21-A)

in its original position was used to re-establish the original position of the section corner stone. (See diagram). (Record: East on a true line bet. Secs. 15 and 22. Var. 19° E. 80. Chs. point 800 ft. above river. Set granite stone $14 \times 14 \times 8$ in. 9 in. in the ground for cor. to Secs. 14, 15, 22 and 23, marked 3 notches on S. and 2 on E. edges and raised a mound of stone alongside. Pits impracticable.)

Also marked a bearing tree which is a pine, 16" in diameter at breast height. On the west side blazed the crown root, put a nail and flasher at the bottom of the blaze and scribed RM in the blaze. Also on the west side made a blaze at breast height and affixed a marked M.A.R.L.S. marker. On the north side made a blaze on the crown root and put a nail and flasher at the base of the blaze. From the section corner monument the N&F on the west side bears $S 85^{\circ} 21' 15''$ E, 79.97 feet and the N & F on the north side bears $S 85^{\circ} 58' 18''$ E, 80.58 feet. Painted all blazes bright red.

