

CERTIFIED CORNER RECORD

Corner 1/4 of sections 6 and 7 T. 9 S. R. 8 E. P.M.M. PARK COUNTY

1. 1883: Rodney W. Page, U.S. Deputy Surveyor. Field notes of... Subdivision Lines of Fractional T. 9 S., R. 8 E.

Set a sandstone 14 x 8 x 6 ins., 9 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a mound of stone alongside. Pits impracticable.

1933: William R. Bandy, U.S. Cadastral Engineer. Field notes of... Resurvey of a portion of... Subdivision Lines of T. 9 S., R. 8 E.

The 1/4 sec. cor., which is a sandstone, 8 x 6 x 6 ins. above ground, marked and witnessed as described in the official record.

2. June 19, 2000: Find a firmly set sandstone, 11 x 6 ins., 8 ins. out of the ground, with 1/4 on S. face (record: N. face) with a 4 1/2 ft. diam. scattering of loose rock around corner. Also find two trees with blaze style which matches bearing trees marked at adjacent corners by Rodney W. Page.

3. In place of stone, set a 2 1/2 ins. diam. by 30 ins. long aluminum pipe, 26 ins. in the ground, with a 3 1/4 ins. diam., aluminum cap, marked as shown below, from which, the trees not of record, but believed to have been blazed and scribed by Rodney W. Page:

- The East trunk of a forked snag, 8 ins. diam., bears N.18°E., 24.7 ft. dist., with scribing "1/4 S6 BT" visible in blaze.
- A Douglas fir, 26 ins. diam. bears N. 87°W., 48.5 ft. dist., with overgrown blaze. We assume this is a scribed bearing tree, although we did not chop open the blaze.

Bury original stone upside-down along East side of monument.


Mark one new bearing object:

- A 3 inch high 'X' on the SW face of a granite boulder, 4 1/2 ft. x 3 1/2 ft., 3 ft. tall, bears N.66°E., 22.8 ft. dist.

Build a 2 1/2 ft. base by 1 ft. high mound of stone, 2 ft. North of corner. Attach "Bearing Tree" and "Land Survey Monument" signs to bearing trees and paint blazes and ring around bearing trees red. Paint "X" on bearing object red.

Corner is located on top of a small ridge which slopes S.33°E.

Resource grade GPS coordinates, NAD27 (+/- 10 m.):
45°04'19.4" N.
110°47'26.6" W.



CERTIFICATION

I, James M. VanAusdol
certify the information shown within is true and correct.
James M. VanAusdol
Signature of Ground Party Chief


I, JANET E. KEMPF
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Signature of Surveyor & Seal

Date: _____ Reg. No. 10806LS

Employer: GALLATIN NATIONAL FOREST

Office of Clerk and Recorder, County of Park This
"corner record" was filed for record on March 13, 2001 @ 1:52
was noted on the cross-index plat and is assigned page No. 108,
in book No. one Danica Nelson
County Official



288798

○ - Corner this sheet

Cross Index No. E-3 T. 9 S. R. 8 E. P.M.M.