

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 28 1/4 | 27 T. 5N R. 9W P.M.M. DEER LODGE County

1. a) 1869 - Walter W. Johnson

Set a granite stone, 24 X 10 X 5 ins., with pits, and marked stone as per instructions,

b) 1919 - Ranney Y. Lyman (G.L.O.)

Found a granite stone 24 X 10 X 5 ins., loosely set, and reset same stone 18 ins. in the ground and marked bearing trees as follows:

A 10" poplar, bears S. 31° E., 49 lks. dist., marked "1/4 S27 BT."
 A 8" poplar, bears N. 53° 30' W., 86 lks. dist., marked "1/4 S28 BT."

2. 1990 - Michael D. Weldon

Found a granite stone, 8" X 5" flush with the ground. Dug down on West side and found "1/4". Both 1919 bearing trees are rotted to ground line.

3. Left original stone reset by 1919 survey in place, and at corner point drilled stone and drove in P-K nail with aluminum washer, marked "7692-S"

I mark two (2) new bearing trees:

A 6" Douglas fir, bears N. 51° E., 41⁰ ft., marked "1/4 S27 BT."
 A 4" Douglas fir, bears N. 87° W., 104² ft., marked "BT."

Set steel post with "Property Boundary" and "Land Survey Monument" decals 1 ft. East of corner stone.

I put red paint, bearing tree tag, "Land Survey Monument" sign, and aluminum washer marked "7692-S" on both bearing trees. Raised a mound of stone 3' base, 2' high East of corner stone. North-South fence 6 ft. East of corner.



CERTIFICATION

I, John K. Bunce, II
 certify the information shown herein is true and correct.
[Signature]
 Signature Ground Party Chief

I, Michael D. Weldon
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)
[Signature]
 Signature of Surveyor & Seal


Date: 4-92 Reg. No. 7692-S

Employer: USDA, Forest Service

SKETCH OF CORNER

Office of Clerk and Recorder, County of DEER LODGE. This "corner record" was filed for record on April 1, 1992 was noted on the cross-index plat and is assigned page No. 293, in book No. 2 By Marianne Strelitz Deputy County Official

Sec. 28



Cross Index No. T-13 T. 5N R. 9W P.M.M.

• - corner this sheet