

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography lies, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CR#1001

CERTIFIED CORNER RECORDATION

Corner 1/4 S10 S15 T. 5N. R. 11W. P.M.M. DEER LODGE County

RECORD
1900

General Land Office Survey, by T.T. Baker & A.B. Knight.


Set stone and marked it 1/4 on south face.

FOUND

Stone clearly marked 1/4 on south face.

SET

From the stone corner, a 4 ins. diam., Douglas fir bears S45W,
1.0 ft. dist., blazed and marked 1/4 S15 BT.



SKETCH OF CORNER

CERTIFICATION


I, _____, certify the information shown herein is true and correct.

Signature Ground Party Chief
Brian D. Thompson
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Signature of Surveyor & Seal
Brian D. Thompson
 Date: 12/16/94 Reg. No. 8795 LS

Employer: _____

Office of Clerk and Recorder, County of Deer Lodge. This "corner record" was filed for record on Dec. 16, 1994 was noted on the cross-index plat and is assigned page No. 370, in book No. 2 by Marian R. Strohbecker Deputy County Official



Cross Index No. F-15 T. 5N R. 11W P.M.M.

• - corner this sheet