

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND AND ORIGINAL RECORD, IF KNOWN:

G.L.O. SURVEY COMMENCED 6-26-1903

RECORD:

SET A GRANITE STONE 20" X 14" X 8"-15" IN GROUND FOR STANDARD COR. OF T5N, R5. 14 & 15 WEST MARKED S.C. 15 N ON NORTH, 14 W. ON EAST, 15 W ON WEST FACE WITH 6 GROOVES ON NORTH, EAST & WEST FACES RAISED A MOUND OF STONE 2' BASE 1 1/2' HIGH NORTH OF COR.

FOUND:

ORIGINAL STONE WITH 6 NOTCHES EAST & WEST


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER:

DATE OF WORK 10-92

SET:

A 2" GALVANIZED CAP ON 1 1/2" X 24" IRON PIPE

SKETCH WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY: (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE)




Surveyor's Seal



I, Gordon E. Sorenson certify that the information shown herein is true and correct, and further certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

DIAGRAM OF CORNER



[Signature] dated: 2/21/97

Gordon E. Sorenson, PE/RLS
Montana Reg. No. 2345ES

[Signature] dated: _____
Field Party Chief

Office of the Clerk and Recorder, GRANITE County, State of Montana:

This "corner record" was filed for record on the 25th day of Feb, 1997, was noted on the cross index plat and is assigned page No. _____ in book No. _____

Time: 9:01 A M.

[Signature]
COUNTY OFFICIAL

34787

CROSS INDEX NO. Z-1, T. 5N, R. 14W, PMM