

**CLASSIFIED LAND CORNER RECORDATION**  
(REFERENCE FSM 7153.53)

**DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)**

Original notes dated August 5, 1873 states, 'Set a post, 4 feet long 4 in. diam. with a mkd. stone 3x3x2 in. buried 12 ins. in the ground and dug pits.

No evidence of the original corner found.

Corner was reestablished by using existing fences, railroad right-of-way, record dimensions of section 1 from the found section corner common to sections 1,2,11,12 and the 1/4 corner common to sections 1 and 6.

**DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

Date of work: MAY, 1979

At the corner point set a 1"x24" iron pipe with a 2" brass cap marked as shown:

No bearing trees in limits. A fence corner bears S.64 W., 100 ft. An east-west fence is south approximately 50 ft.



**SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)**

See Certificate of Survey No. 81.

Surveyor's Seal




I, William D. Bayer certify that the information shown herein is true and correct.

William D. Bayer  
Signature of Ground Party Chief

I, William D. Bayer certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

William D. Bayer  
Signature of Surveyor

**DIAGRAM OF CORNER:**



● = Corner recorded on the sheet

33215  
Registration Number

Office of Clerk and Recorder, County of Granite

This "corner record" was filed for record on the 21st day of May, 1979, was noted on the cross-index plat and is assigned page No....., in book No.....

M. J. Lawrence  
County Official

Cross Index No. C-21 T. 6N R. 14W PM Mer.