

CLASSIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record: Set a quartzite stone 22x17x4 ins. buried 15 ins. in the ground. No bearing trees.

Found the original stone lying face up under fence. Stone is clearly mkd. $\frac{1}{4}$.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 12-17-79


At the corner point set a #5 rebar with an aluminum cap. Placed the original stone alongside the rebar.

A fence post bears North 4.2 ft. with a bearing tree sign attached.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. 115

Surveyor's Seal




I, William D. Bayer, certify that the information shown herein is true and correct.

Signature of Ground Party Chief: William D. Bayer

I, William D, Bayer, certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor: William D. Bayer

DIAGRAM OF CORNER: T.7 N., R. 14 W. N.



• = Corner recorded on the sheet

3321 S Registration Number

100003

Office of Clerk and Recorder, County of Granite

This "corner record" was filed for record on the 18th day of January 1980, was noted on the cross-index plat and is assigned page No., in book No.

County Official: Marie Hanson

Cross Index No. G-21 T. 7N R. 14 W Mer.