

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner N 1/4 Cor. Sec 24 T. 8N R. 25E P.M.M. Musselshell County

1) GLO dependent resurvey. - Set an iron post 3 ft. long, 1 in. diam. 30 ins in the ground for the 1/4 sec. cor. with a ~~the~~ brass cap marked

1/4 513
4 524
1943.

2) Found brass cap as described.

3) No additional work to perpetuate the corner position

SKETCH OF CORNER

CERTIFICATION

I, Dan Kenczka
certify the information shown herein is true and correct.
Dana Kenczka
Signature Ground Party Chief


I, Jack R. Fisher
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)
Jack R. Fisher
Signature of Surveyor & Seal

Date: 2/18/89 Reg. No. 60135
Employer: Thomas Dean & Hopkins

of Clerk and Recorder, County of Musselshell. This "corner record" was filed for record on the February 14 day of 1990 11:05 P.M. was noted on the cross-index plat and is assigned page No. _____, in book No. _____

Frances L. Dawson
County Official

Cross Index No. N-23 T. 8N R. 25E P.M.M.



• - corner this sheet