

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Sections 36 & 31 T. 8N R. 26 & 27E P.M.M. Musselshell County

ORIGINAL RECORD: (1884 G.L.O.) Corner set; notes illegible.

SUBSEQUENT RECORD: (1904 G.L.O.) Found a sandstone 6x8x2 ins. properly marked; replaced with a sandstone 18x15x6 ins. 14 ins. in the ground marked with 6 notches on W. and E. edges, and raise a mound of stone 2 ft. base 1 1/2 ft. high N. of cor., from which:
A pine 15 ins. diam. bears N40°E, 1.35 chs. dist., marked T8N R27E S31 BT.

SUBSEQUENT RECORD: (1906 G.L.O.) The cor. of Ts.8N. Rs. 26 and 27 E. which is a sandstone 10x14x3 ins. above ground, marked and witnessed as described by the surveyor general.

SUBSEQUENT RECORD: (1953 B.L.M.) The corner of Ts. 8N, Rs.26 and 27 E., which is monumented with a sandstone 20x18x8 ins., firmly set, plainly and properly marked and witnessed by the northeast bearing tree.
At the corner point, set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with brass cap; from which:
An old bearing tree: A pine 20 ins. diam. bears N46°45'E, 1.36 chs. dist., marked T8N R27E S31 BT.
Mark new bearing tree: A pine 9 ins. diam. bears N19°W, 2.80 chs. dist., marked T8N R26E S36 BT.
Bury the old corner stone alongside the iron post.

EVIDENCE FOUND: Found a 3 1/4" brass cap, which is leaning to the north marked as shown in the sketch below, on the north side of an east-west fenceline with BT trees burnt from a fire.

PERPETUATION: Left brass cap as found. The corner is approximately 0.17 miles west of a gravel road.

Date of Survey: July, 2007.

Compass Declination Used:

NAD 83 coordinates for this corner:
Latitude = 46°23'51.3152"N Longitude = 108°24'14.7667"W
NOTE: These coordinates are to be used as a search tool only.



(Not to Scale)
SKETCH OF CORNER

CERTIFICATION

I, Steve Cummings
certify the information shown herein is true and correct.

Signature Ground Party Chief

I, Kurt A. Luebke
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Signature of Surveyor & Seal

Date: _____ Reg. No. 13237 S

Employer: DJ&A P. C.

Office of Clerk and Recorder, County of Musselshell. This "corner record" was filed for record on _____ was noted on the cross index plat and is assigned page No. _____, in book No. _____

County Official

Cross Index No. Z-25 T. 8N R. 26E PMM
Cross Index No. Z-1 T. 8N R. 27E PMM

Sec. 36

● - corner this sheet