

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

The east boundary of Township 14 North Range 18 East was retraced by George Stafford in 1886, having been originally surveyed in 1882 by George Robinson (west boundary T.14N., R.19E.). The corner for Sections 1 and 12 (NE S.12) was a 14" x 12" x 5" sandstone. This corner was obliterated by county road construction. Mr. R.A. van der Hagen, Sr. was consulted and his recollection was that the corner was on the existing old east-west fence and would have fallen in the west road ditch.


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 8/86

The existing east west fence was used for latitudinal position and a straight line intersecting the extension of that fence between the W 1/4 Corner of Section 6 (stone) and the SE Corner of Section 12 (stone). At the intersection, set a 5/8" x 24" rebar with plastic cap with a mound of stone around the point. The corner falls approximately 4' west of the west edge of a new cattleguard.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



I, J. Kip Gjerde, PE, LSIT certify that the information shown herein is true and correct.

Signature of Ground Party Chief

DIAGRAM OF CORNER:

N. NE Cor. S.12 T.14N., R.18E.

I, James L. Fletcher, ES certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

= Corner recorded on the sheet

5201ES Registration Number

Office of Clerk and Recorder, County of FERGUS

This "corner record" was filed for record on the SEP 29 1986 day of 19, was noted on the cross-index plat and is

signed page No. 122, in book No. 2

County Official signature

25012

Cross Index No. E-25 T. 14 R. 18 Mer.

