

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner SW cor. Sec. 10 T. 18 N., R. 27 W. P.M.M. Mineral County

Record 1893 GLO - A Quartzite stone 16x14x6 ins. 11 ins. In the ground, ... 4 notches on S. and 3 notches on E. edges from which;
 a 30" pine bears N. 16½ E. 73 links
 a 12" pine bears S. 59½ E. 51 links
 a 28" Tamarack bears S.60 W. 40 links
 a 16" tamarack bears N.38 W. 125 links

1945 Location Tag placed on small fir tree near corner.

1964 Bergren set 2" Brass cap with 4 new RM trees
 a 12" P. Pine bears N.23 E. 74 links,
 a 10" D. Fir bears S. 61 E 74 links,
 an 8" D. Fir bears S.8 W. 77 links,
 a 12" P. Pine N.54 W. 26 links.

Filed Cor. Recordation.

1971 BPR road plans show tie to found section corner.

1984 Unknown Individuals place tags on trees in vic. of corner. No corner Recordation filed.

Found: May 27, 1999 We find 2 ½ " brass cap marked as shown firmly set. 0.4' protruding from the ground.

Accessories:

- A 15" D. Fir bears West 1.3 ft w/ USFS location tag " Approx. Sec. Cor. 9-20-45 CHS"
- A rotten pine stump bears N.55 W 16.8 feet no marks or tags.
- A 12" pine bears N.12 E. 4.6 feet w/ USFS Loc. Tag "South 5.25 feet 1984" by ?
- A 12" fir bears S.57 E. 48.5 feet, w/ unmarked USFS 54-3 sign
- A 17" p. pine bears S.6 E. 26.0 feet, Healed blaze, MARLS tag "N.59½ W 33.7" " No Name./ date. Note discrepancy.
- A 12"fir bears S.22 W. 49.2 feet. Healed blaze, unmarked USFS 54-3 sign.
- A 27" stump bears S.64 W. 26.0 feet. Scribed " 18NR27W S16 BT" Marls Tag:"N.60 E 26.4" No name or date.
- A 4"x4" concrete R/W marker bears S.9 W. 13.7 feet.

Placed USFS 54-9 sign on the 12" Pine that is N.12 E 4.6 feet from corner.

Used Silva ranger Compass Decl. 20deg. East, and cloth tape

See reverse for Diagram



Fnd. 2 1/2"
Brass Cap

SKETCH OF CORNER

CERTIFICATION

I, Donald M. Roedel
certify the information shown herein is true and correct.

Signature of Ground Party Chief

I, Donald M. Roedel
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (22-101, et seq., MCA)

Signature of Surveyor & Seal
 Date: 6/15/99 Reg. No. 10998LS

Employer: MDT

Sec. 10

Office of Clerk and Recorder, County of Mineral This "corner record" was filed for record on November 14, 2000 @ 10:30 AM was noted on the cross-index plat, and is assigned Page No. _____, in Book No. _____

Katherine Jasper by Mary Uarnall
County Official
Fee Exempt

Cross Index No. J13 T. 18 N. R. 27 W., PMM