

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

(RECORDED) SET A POST 4 1/2 FT X 4 INS.

(FOUND) POST 2" SQ DRIVEN IN GROUND WITH 3" PIPE LYING ON GROUND AND 3 R.M. TREES MARKED BY OTHERS.

NO TRACE OF ORIGINAL B.T.'S

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7/22/76


SET 30 IN. X 1 1/2" GALV. PIPE WITH BRASS CAP.
20" Y. PINE BEARS N 82° E 41.4 FT DIST.
18" FIR BEARS S 49° E 29.0 FT. DIST.
17" Y. PINE BEARS S 58° W 26.5 FT. DIST.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



DIAGRAM OF CORNER:

N. 120° R 26 W



= Corner recorded on the sheet

Surveyor's Seal



I, _____ certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, H. GENE WARREN certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

H. Gene Warren
Signature of Surveyor

2734-5
Registration Number

Office of Clerk and Recorder, County of Sandus

INDEXED N
3:42 P.M.

138316

This "corner record" was filed for record on the 2 day of August 1976, was noted on the cross-index plat and is assigned page No. 565, in book No. 1

Allyce Vaughn Clerk Rec.
County Official by Earlyn Cox Dep

VOL 1 PAGE 505

Cross Index No. R-5 T. 20 N R. 26 W Mer.