

INSTRUCTIONS

1. Original and/or subsequent rec. locate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 1/4 S16 | S15 T. 21N. R. 29W. P.M.M. Sanders County

GLO RECORD (1889): Set a post, 3 ft. long, 4 ins. square, 24 ins. in ground for 1/4 sec. cor., marked 1/4 on West face...established 2 BTs.

FOUND - 1989 (100 anniversary of corner): We find no evidence of original post or BTs however, we find a smooth, 5/8" diam. iron pin with a 2" aluminum cap stamped as indicated ("Dept. of Highways - Montana") and no markings indicating corner position etc. , from which:

- * A 20" pine bears N.20°W., 17.8 ft. Trees is marked with a nail with flagging in a 4" x 10" blaze, 3 ft. above the ground, no scribing is visible.
- * A 20" pine bears N.73°W., 10.6 feet. Tree is marked with a nail with flagging in a 5" x 7" blaze, 3 ft. above the ground, no scribing visible.
- * A 6" fence post bears N.10°E., 7.3 feet.
- * We set a steel post w/standard MDOH decal 1.0 feet North of corner.

An old, downed fence line extends to the South.

See Certificate of Survey No. 995



Markings on found aluminum cap.

3 PAGE 1

SKETCH OF CORNER

CERTIFICATION

I, Duane Schmitz

certify the information shown herein is true and correct.

Duane Schmitz
Signature Ground Party Chief

I, Richard A. Amisworth

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101 et seq., M.C.A.)

[Signature]
Signature of Surveyor & Seal


Date: 11/89 Reg. No. 2923S

Employer: PROFESSIONAL CONSULTANTS

Office of Clerk and Recorder, County of Sanders. This "corner record" was filed for record on the 12 day of Jan 19 90, was noted on the cross-index plat and is assigned page No. 337, in book No. 3

Dixie Vaughn, Clerk
County Official

Cross Index No. L13 T. 21N R. 29W P.M.M.



• - corner this sheet