

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner S15 1/4 | S14 T. 21N. R. 29W P.M.M. Sanders County


GLO RECORD (1889): Set a post, 3 ft. long, 4 ins. square, 24 ins. in ground for 1/2 sec. cor. 2 BTs established.

RECORD - 1974 (Corner Recordation Form - Ainsworth, PLS #2923S): We find no evidence of original post or BTs. We establish this corner by single proportion between Northwest and Southwest corners of Sec. 14. Position for corner falls in North-South line of piled rock (old fence line). New fence is 30 feet West of rock line. To perpetuate this corner we set an 18" x 1 1/2" BC and raise a mound of stone. No RMs established.

FOUND - 1989 (100th anniversary of corner): Found a 3/4" pipe with a 1 1/2" Brass Cap, marked as indicated below, in a rock mound. There are numerous rock mound in a North-South line which appears to be an old fence line. An existing fence (North-South) falls 30 feet to West. As there are no trees or other bearing objects within limits, no RMs were established.

We set a steel post w/standard MDOH decal 1.8 feet North of monument and rebuild the mound of stone.

See Certificate of Survey No. 995



Markings on found aluminum cap.

3 PAGES


SKETCH OF CORNER 2923S

CERTIFICATION
 I, Duane Schmitz
 certify the information shown herein is true and correct.
Duane Schmitz
 Signature Ground Party Client
 I, Richard A. Ainsworth
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)
Richard A. Ainsworth
 Signature of Surveyor & Seal
 Date: 11/89 Reg. No. 2923S
 Employer: PROFESSIONAL CONSULTANTS

Office of Clerk and Recorder, County of Sanders. This "corner record" was filed for record on the 12 day of Jan 1990, was noted on the cross-index plat and is assigned page No. 3, in book No. 335

County Official
Sally Clawson, Dep.

Cross Index No. L17 T. 21N R. 29W P.M.M.



• - corner this sheet