

INSTRUCTIONS

1. Original and/or subsequent record us [unclear] date the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner S10|S11 S15|S14 T. 21N. R. 29W. P.M.M. Sanders County

GLO RECORD (1889): Set a 4 ft. post, 5 ins. square, 24 ins. in ground for cor. to secs. 10,11,14 & 15....established 4 BTs.

RECORD, 1974 (Corner Recordation Form by Ainsworth, PLS #2923S):

We find no evidence of original post or bearing trees. We find an 8" x 8" fence post with fences going South and West. We accept this fence corner as the best evidence of original corner. To perpetuate this corner we set an 18" x 1 1/2" BC next to fence corner and establish the following reference monuments:

- A pine tree 16" bears N.59°30'W., 205.0 ft.
- A triple pine 18" bears N.02°15'W., 199.0 ft.

FOUND - 1989 (100th anniversary of corner): We find a 3/4" iron pipe with a 1 1/2" brass cap, 0.1 ft. below surface, 0.6' North of fence corner. (fence runs North & West). Cap marked as indicated below.

From which:

- \* A 19" pipe bears N.58°W., 204.6 ft. w/partially closed blaze, scribing visible but not legible. large "X" cut at DBH. We mark w/K tag.
- \* A leaning, dead snag bears N.02°E, 198.0 ft., scribed "RM" at base.
- \* An 8" pine bears N.20°E., 158.2 feet. We blaze and scribe "RM". Mark with K tag.
- \* A steel post w/standard MDOH decal bears SW, 0.6 ft....at fence corner post.

See Certificate of Survey No. 995



3 PAGE 78


SKETCH OF CORNER

CERTIFICATION  
 I, Duane Schmitz  
 certify the information shown herein is true and correct.  
Duane Schmitz  
 Signature Ground Party Chief  
 I, Richard A. Ainsworth  
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-10) et seq., M.C.A.  
Richard A. Ainsworth  
 Signature of Surveyor & Seal  
 Date: 11/89 Reg. No. 923S  
 Employer: PROFESSIONAL CONSULTANTS

Office of Clerk and Recorder, County of Sanders. This "corner record" was filed for record on the 12 day of Jan 1990, was noted on the cross-index plat and is assigned page No. 3, in book No. 338

Sally Clauson, Deputy  
 County Official

Cross Index No. J17 T. 21N R. 29W P.M.M.



• - corner this sheet