

INSTRUCTIONS

Q:CO-STD/152
Created 4/8/92

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Section Corner 11, 12, 13, and 14 T. 22N R. 30W P.M.M. Sanders County

RECORD

GLO 1889: Set a post 4 ft. long 5 ins. Square, 24 ins. In the ground, for cor. to secs. 11, 12, 13, & 14, marked

- T22N S12 on NE
- R30W S13 on SE
- S 14 on SW, and
- S11 on NW faces, with 4 notches on S. and 1 on E. edges, from which:
 - A tamarack tree, 20 ins. diam., bears N.35°20'E., 97 lks. dist. marked T22NR30WS12BT.
 - A fir tree, 20 ins. diam., bears S.69°20'E., 20 lks. dist. marked T22NR30WS13BT.
 - A tamarack tree, 20 ins. diam., bears S.40°10'W., 27 lks. dist. marked T22NR30WS14BT.
 - A tamarack tree, 18 ins. diam., bears N.75°30'W., 69 lks. dist. marked T22NR30WS11BT.

Wheeler, Found badly burnt stump with scribing visible in NE quadrant.
394-ES, 1974 Set a 2-1/2" x 36" pipe with brass cap, from which:

- A 10" tamarack, bears N.3°E., 25.50 feet
- A 5" fir, bears S.59°E., 40.00 feet
- A 3" tamarack, bears S.38°W., 24.30 feet
- A 8" tamarack, bears N.68°W., 17.50 feet

FOUND

- 2001: Found 3" diameter brass cap on a 2-1/2" pipe 2" above the ground.
From which:
 - A 18" fir, bears S.26°E., 17.25 feet with visible blaze (RM1)
 - A 10" fir, bears S.25°W., 13.78 feet, with visible blaze (RM2)
 - A 11" fir, bears N.65°W., 27.42 feet with visible blaze (RM3)
 - A 3' tall steel post bears N.66°E., 0.1', with a metal tag "tied to AVISTA CORP RES BNDY, GPS NAD 83, LS 5616 1999"


TO PERPETUATE:

Paint, blaze, and tag trees. See Certificate of Survey on file at Sanders County Courthouse.

		<p>CERTIFICATION</p> <p>I, <u>Kevin Cassidy</u> certify the information shown herein is true and correct.</p> <p><i>Kevin Cassidy</i> Signature Ground Party Chief</p> <p>I, <u>R. A. Ainsworth</u> certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)</p> <p><i>Richard A. Ainsworth</i> Signature of Surveyor & Seal 2923 S</p> <p>Date: 8/2001 Reg. No. 2923 S</p> <p>Employer: Professional Consultants, Inc.</p>
--	--	---

SKETCH OF CORNER

Sec. 11



254629 BOOK: 5 CORNER REC PAGE: 38 Pages: 0
STATE OF MONTANA SANDERS COUNTY
RECORDED: 03/02/2004 9:44 KOI: COR RECORD
PAT INGRAHAM CLERK AND RECORDER
FEE: \$0.00 BY: *Pat Ingraham*
TO: PROFESSIONAL CONSULTANTS, INC. P.O. BOX 1750, MISSOULA, MT