

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the position for the 1/4 of sections 16, 15 T. 23 N., R. 30 W., I find a 6 inch by 5 inch shattered shale stone with 1/4 on N. face and rotted remains of squared stake in the ground under the stone. From which a 21 inch fir bears S. 70° E., 13 lks. (8.6) ft. marked 1/4 S; the rest is grown over. Rotten stump remains bears N. 80° W. and 17 lks. (11.22 ft).

Record 1893 : Set a 3 foot by 3 inch squared stake 24 inches in the ground. From which a 10 inch fir bears S. 73° E., 13 lks., a 12 inch fir bears N. 80° W., 17 lks., both trees marked 1/4 S. BT.


Record 1906: A 7 inch by 8 inch by 12 inch stone with 1/4 on North face from which a 20 inch pine bears N. 10° E., 64 lks. (42-24⁵); a 12 inch fir bears S. 70° E. and 150 feet (99 feet) both trees marked 1/4 S. BT.

Note: The 1906 bearing tree positions are obliterated by a gravel pit and a road.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set a 2 inch by 30 inch brass capped iron pipe 24 inches deep in the ground from which a 14 inch fir bears N. 22 3/4° E. and 8.4 feet dist. A 7 inch fir bears N. 83° W. and 19.4 feet dist. Both trees blazed and scribed R.M. Posted BT, Attention, and survey monument signs. Painted blazes and iron pipe red, raised a mound of rock around the iron pipe.

Date of work: 8/21/74



SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



I, William W. Markham, certify that the information shown herein is true and correct.

William W. Markham


Signature of Ground Party Chief

I, Stanley J. Skousen, certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen

Signature of Surveyor

DIAGRAM OF CORNER: R 30 W



● = Corner recorded on the sheet

2532 S Registration Number

137386

Office of Clerk and Recorder, County of Sanders, 10:00 am

This "corner record" was filed for record on the 28 day of April 1976, was noted on the cross-index plat and is assigned page No. 534, in book No. 1

Digit thought by Linda Lourse
County Official

Cross Index No. L 13 T. 23 N. R. 30 W. Mer.

VOL

PAGE 534