

CERTIFIED CORNER RECORDATION

Corner $\frac{1}{4} \frac{6}{7}$ T. 26N. R. 18W. P.M.M. Lake County

GLO Record, Book 2717 Page 33

"Set a limestone 14X7X7 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face from which

A White pine 14 ins. diam. bears N.16°10'W. 14 lks. distant marked 1-4 S. B. T.

A White pine 18 ins. diam. bears S.10°10'W. 20 lks. distant marked 1-4 S. B. T."

1974 Certificate of Survey No. 2270 - Doyle

"Rebar set by proportion"

Evidence Found this Survey

Found 1 1/4" Doyle yellow plastic cap on a 5/8" X 24" rebar.

1996 Remonumentation by S. R. Smith

At the position marked by the Doyle rebar, set an aluminum pipe 2 1/2" diameter, 30" long with 3 1/4" diameter aluminum cap, marked as shown below. Placed the Doyle rebar inside aluminum pipe.

New bearing trees established this survey:


A 1 1/4" diameter yellow plastic cap marked "SMITH 4740S", set in a 11" diameter lodgepole pine, scribed "1/4 S7 BT", bears S. 62° W., 29.58' dist.


A 1 1/4" diameter yellow plastic cap marked "SMITH 4740S", set in a 12" diameter alpine fir, scribed "1/4 S7 BT", bears South, 28.63' dist.

Bearings listed in remonumentation section were measured with a hand compass, declination 17 1/2' East.

All new bearing trees marked with a snow blaze, notch at base of scribing and Bearing Tree sign. Bearings and distances are to center of tree.

Refer to the Certificate of Survey filed in conjunction with this corner recordation for ties to adjacent section controlling corners in the area.





CERTIFICATION

I, Thomas E. Stark
certify the information shown herein is true and correct

Thomas E. Stark
Signature Ground Party Chief

I, S. R. Smith
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-10), et seq., M.C.A.

S R Smith
Signature of Surveyor & Seal

Date: 12/31/96 Reg. No. 4740S
Employer: Smith Surveying

Office of Clerk and Recorder, County of Lake. This "corner record" was filed for record on JAN 17 1997 at 11:00 AM

was noted on the cross-index plat and is 379400, in

C-2094

RUTH E. HODGES

County Official

Cross Index No. E-3 T. 26 N. R. 18 W. P.M.M.

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

Sec. 7

◀ corner this sheet

Judy [unclear] dep
see n/c