

CR # 846
330403

CERTIFIED CORNER RECORDATION

Corner SE SECTION 26 T. 30N R. 29E P.M.M. PHILLIPS County

ORIGINAL RECORD: (Page & Page, 1891) Set a granite stone 14 x 12 x 5 ins, 10 ins. in the ground for corner to sections 25, 26, 35 and 36 marked with 1 notch on South and East edges; dug pits 18 x 18 x 12 ins. in each section 5 1/2 ft distant and raised a mound of earth 2 ft. high 4 1/2 base alongside.

SUBSEQUENT RECORD: This corner is shown as found on 3 different recorded surveys, but none indicate what was found or set.

EVIDENCE FOUND: Found 1/2" rebar 10" above ground surface at East base of a fence corner post North by West.

PERPETUATION: Held rebar as best evidence for corner and replaced with a Montana Department of Transportation aluminum monument. Set MARLS tag on fence corner post and set a 1" dia. pipe, 3 ft. long, 3 ft. North of corner with MDT sticker attached.

SEE ASSOCIATED CERTIFICATE OF SURVEY

SKETCH OF CORNER

03-558 MP154

CERTIFICATION

I, _____
certify the information shown herein is true and correct.

Signature Ground Party Chief

Scott C. Koterba

I, _____
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Scott C. Koterba
Signature of Surveyor & Seal

Date: 4/29/04 Reg. No. 10801 LS

Employer: Milestone Surveying

Office of Clerk and Recorder 330403 B-CR P-0846
 record' was filed for record PHILLIPS COUNTY MONTANA Fee \$.00
 was noted on the cross-index Filed 05/04/2004 At 04:38 PM
 book No. _____ Laurel N Hines, Clerk and Recorder
 By *Stephanie M. Ross*, Deputy

County Official

Cross Index No. V21 T. 30N R. 29E PMM

Sec. 26

• corner this sheet