


INSTRUCTIONS

1. Original and/or a true and correct record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner N $\frac{1}{4}$ Section 29 T. 35N R. 55E P.M.M. Sheridan County

1. Had a copy of G.L.O. Plat.
2. Found iron pipe below paved road surface.
Monument fits existing features.
3. Set p.k. nail on paved road surface.
Monument is in centerline of east-west paved road.
Fence line goes south.



CERTIFICATION

I, _____ certify the information shown herein to be true and correct.

Signature of Third Party: Richard H. Hon

I, _____ certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (30-2-101 M.C.S.A.).

Signature of Surveyor & Seal: [Signature]

Date: 1/95 Reg. No. 9018S


Employer: Interstate Engineering, Inc.

Office of Clerk and Recorder, County of Sheridan. This "corner record" was filed for record on January 30, 1995 at 11:00 AM was noted on the cross-index plat and is assigned page No. _____, in book No. 214

441433

Milton E. Koulouk
County Official
by Dennis Koulouk Deputy DH

Cross Index No. R-7 T. 35N R. 55E P.M.M.



• - corner this sheet