

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 1/4 Cor Sec 22-27 T. 35N R. 6E 55E P.M.M. Sheridan County M

Iron pin in center of county road
also center of section 22 reset by
steel pin capped No. 49765.

CERTIFICATION

I, _____
certify the information shown herein is true and correct.

Signature Ground Party Chief

I, _____
certify that this Corner Record correctly represents work performed
by me or under my direction in compliance with the "Corner
Recordation Act" (70-22-101, et seq., M.C.A.)

C. V. Best

Signature of Surveyor & Seal

Date: April Reg. No. 5465

Employer: 1985


SKETCH OF CORNER

Office of Clerk and Recorder, County of Sheridan. This "corner
record" was filed for record on April 10, 1985 at 4:00 pm
was noted on the cross-index plat and is assigned page No. _____, in
book No. _____
Milton E. Whuland
County Official

415976

#65

Cross Index No. R 15 T. 35N R. 55E P.M.M.



• - corner this sheet

Sec 27