

**CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

From: "Retracement of Subdivision of T9S, R8E". 1914. (6848-69)

The retracement survey found "a sandstone, 6x5x9 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General" in 1883. (original record: 1697-456)

During this survey, I found an irregular volcanic stone 6x5x6 ins. above ground, at the base of an old corner post in a mound of rock covered by sagebrush duff. From this point, a down jackleg fence runs northerly and a row of old posts runs easterly. The stone is marked with 1 notch on the east face and 4 notches on the south face.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 4/476

Cut an "x" on top of the stone.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See drawing on reverse of corner record for NW corner of Section 14.

Surveyor's Seal

I, \_\_\_\_\_  
certify that the information shown herein is true and correct.

\_\_\_\_\_  
Signature of Ground Party Chief

I, Henry A. Rate  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Henry A. Rate  
\_\_\_\_\_  
Signature of Surveyor

DIAGRAM OF CORNER:

N. T9S  
R8E  
MPM

11	12
14	13

= Corner recorded on the sheet

3716S  
Registration Number

Office of Clerk and Recorder, County of Park 142567

This "corner record" was filed for record on the 27<sup>th</sup> day of October 1976, was noted on the cross-index plat and is assigned page No. 11, in book No. one

Margaret Troniceal  
County Official