

**CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

From: "Subdivisional lines of T9S, R8E". 1883. (1697-453)

"Set granite stone 14x12x10 ins., 9 ins. in the ground .....marked 3 notches on S and 1 on E edges, and raised a mound of stone alongside."

Found: A triangular-shaped granitic stone, 10x7 in., 6 ins. out of the ground, marked with 3 notches on the south face and 1 notch on the east face. Stone firmly set, but leaning downhill (south). Large cairn along south side of stone.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7/12/76

Cut an "x" on top, straighten, reset. Set a rebar along the south face (downhill) for support and magnetic response. Rebuilt a mound of stone over corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See drawing on reverse of corner record for NW corner of Section 14.

Surveyor's Seal

I, .....  
certify that the information shown herein is true and correct.


Signature of Ground Party Chief

I, Henry A. Rate  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

*Henry A. Rate*

Signature of Surveyor

DIAGRAM OF CORNER:



= Corner recorded on the sheet

3716S  
Registration Number

Office of Clerk and Recorder, County of Park 142569

This "corner record" was filed for record on the 27 day of October 1976, was noted on the cross-index plat and is assigned page No. 13, in book No. one

*Margaret Monical*  
County Official

Form 125-3690

Cross Index No. 2-21 T. 9 R. 8E Mer.

*Fee - 50 cents*